

PO BOX 16458 • FRESNO CA 93755

MATERIAL SAFETY DATA SHEET

PRODUCT/TRADE NAME:

AMMONIUM NITRATE 34-0-0

I. NAME

PRODUCT/TRADE NAME: AMMONIUM NITRATE 34-0-0

EPA REGISTRATION #: NONE CHEMICAL NAME/COMMON NAME: Ammonium Nitrate/Ammonium Nitrate

II. HAZARDOUS INGREDIENTS

CAS# OSHA PEL ACGIH TLV Ammonium Nitrate 6484-52-2 NE NE

III. PHYSICAL DATA

SPECIFIC GRAVITY (H2O = 1): NA

MELTING POINT: NE

VAPOR DENSITY (AIR = 1): NA

% VOLATILES BY VOL.: NA

ODOR: Odorless

APPEARANCE: White Crystals FLASH POINT/METHOD: NA

VAPOR PRESSURE (mmHg): NA SOLUBILITY IN H2O: Miscible

IV. FIRE & EXPLOSION HAZARD

EXTINGUISHING MEDIA: [X] Water Fog [] Foam [] Alcohol Foam

[] CO2 [] Dry Chemical [] Other FIRE FIGHTING PRECAUTIONS & HAZARDS:

Fight fire upwind. Wear positive pressure self-contained breathing apparatus and full protective equipment. Avoid breathing smoke or mist. Avoid fallout and runoff. Dike to prevent entering drains, sewers, or water courses. Evacuate

people downwind from fire.

V. CARCINOGEN STATUS

[] OSHA [] NTP [] IARC [X] No Listing Type

VI. REACTIVITY

[X] Stable HAZARDOUS POLYMERIZATION

[] Unstable [] May Occur [X] Will Not Occur

AVOID: Bases oxidizers, potassium chlorate, potassium nitrate, chlorine,

hypochlorates

HAZARDOUS DECOMPOSITION PRODUCTS: COx, SOx, NOx, NH3, POx

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL: Vacuum or sweep up and place into disposal container.

DECONTAMINATION: Treat spill area with detergent and water. Repeat procedure as necessary until area is clean.

ENVIRONMENTAL HAZARDS: May be toxic to aquatic organisms. Dike to prevent entering drains, sewers or water courses.

DISPOSAL: Dispose of in accordance with Federal, State and local regulations.

VIII. HEALTH PRECAUTION DATA

INGESTION: Do not ingest. Wash thoroughly before eating, drinking or smoking. INHALATION: No PEL/TLV established for this product. Wear proper respiratory protection for exposures above the nuisance particulate levels of PEL/TLV 15 mg/m3 total dust 5 mg/m3 respirable dust. May be irritating to the respiratory tract.

SKIN ABSORPTION: Can cause skin irritation. Wear proper personal protective equipment to reduce skin exposure.

EYE EXPOSURE: Keep out of eyes. Can cause eye irritation. Wear proper eye protection. If exposed, flush eyes for a minimum of 15 minutes with water. EFFECTS OF OVEREXPOSURE: Can cause respiratory tract and eye irritation. Ingestion could cause corrosive deterioration of digestive system tissue and ingestion of large amounts may result in vomiting and diarrhea and excessions.

sive fluid loss. No known chronic effects. Preexisting medical conditions involving the above symptoms may be aggravated by exposure..

FIRST AID: In all cases, get prompt medical attention. If ingested, give several glasses of water and induce vomiting. Do not induce vomiting if person is unconscious. For skin exposure, remove contaminated clothing and wash with soap and water. For eye contact, irrigate for a minimum of 15 minutes with

IX. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear only NIOSH/MSHA - approved respiratory protection for nuisance particulates up to 10 times the PEL/TLV. Positive pressure self-contained breathing apparatus should be used for confined space entry and high exposure operations.

water. If inhaled, remove victim to fresh air, and administer CPR if necessary.

PERSONAL PROTECTIVE EQUIPMENT: Work gloves, safety goggles or glasses with side shields and brow protection.

VENTILATION: General ventilation to control nuisance dust.

X. SPECIAL PRECAUTIONS

Keep out of the reach of children. Read and follow all label instructions. May be corrosive to copper, brass, steel, aluminum and concrete.

XI. REGULATORY DATA

REGULATORT DATA						
SARA HAZARD CLASS: [] Acute [] Chronic [] Flammable						
		[] Pressi	ure [] Reac	tive [X]	None
SARA 313:	[] Yes	[X] No	Chemic	:al:		
SARA 302:	[] Yes	[X] No	Chemic	:al:		
TPQ:						
CERCLA:	[] Yes	[X] No	Chemi	cal:		
RQ:						
RCRA:	[] Yes	[X] No				
NFPA HAZARD RATING:				NFPA HAZARD RATING SCALE:		
Health:				0 = Minimal		3 = Serious
Fire:	: :			1 = Slight		4 = Severe
Reactivity: [0]				2 = Moderate		4 - Severe
Special:				Z = Woderate	,	
HMIS CODES:				HMIS HAZARD RATING SCALE:		
	[1]			0 = Minimal		3 = Serious
Fire:				1 = Slight		4 = Severe
Reactivity:	[0]			2 = Moderate	j	

DATE PREPARED: November 8, 1989 REVISED DATE: August 28, 2002

Notice: This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

*Technical Material NE - Not Established NA - Not Applicable

24 Hour Emergency Phone Number CHEMTREC: (800) 424-9300

